




BLANKA ANGOLO




BLANKA ANGOLO PL



BLANKA ANGOLO G



BLANKA ANGOLO PL G



BLANKA ANGOLO-1

PL = Top connection

## PRODUCT INFORMATION:

Thermal energy:	72,7 kWh,	PL: 74,2 kWh
Energy efficiency:	87 %,	PL: 88 %
CO%:	0,09 %,	PL: 0,09 %
Heat storage capacity:		
	100% after 8,2 hours,	PL: after 8,6 hours
	50% after 26,9 hours,	PL: after 28,2 hours
	25% after 45,2 hours,	PL: after 47,4 hours

## PRODUCT NUMBER:

Product	Product number	Weight kg	Height mm
BLANKA ANGOLO	3KT	1880	1824
BLANKA ANGOLO-1	3KT-1	1935	1824
BLANKA ANGOLO PL	3KTP	1960	1824
BLANKA ANGOLO G	3KTG	1900	1824
BLANKA ANGOLO PL G	3KTPG	1985	1824

## NEEDED FOR ASSEMBLY:

\* Mortar 1 x 25 kg (not included in NunnaUuni delivery)

## NOTE!

See the product pictures of PL and glass models (G) from the 3pdf!

## PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES <sup>(1)</sup>				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø	Temperature °C
Blanka Angolo / Blanka Angolo G	-	-	33	20	-	203	-12	17	160	310
Blanka Angolo PL / Blanka Angolo PL G	-	-	33	20	-	176	-12	17	180	310

## FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]				FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR			
	approx. 150x150	approx. 150x200	approx. 150x300	round Ø	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT	Burning air approx. m³/h
Blanka Angolo / Blanka Angolo G	-	x	x	160-210	150-180	250	350	662	-	920006	70-100
Blanka Angolo PL / Blanka Angolo PL G	-	-	-	180	-	-	-	662	-	920006	70-100

## SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250			
	Behind	On the sides	Top	Front
Blanka Angolo / Blanka Angolo G	50	300	200	1000
Blanka Angolo PL / Blanka Angolo PL G	50	300	200	1000

<sup>1)</sup> The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.

### Take a notice of the countryspecific approvals in section 3

#### NOTES!

The flue heat category required by the fireplace is T400.

The recommended minimum flue height is 5 m with Ø180 mm. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue. In the picture you can see the Finnish version.

### Country- and region-specific regulations must be adhered to when installing the fireplace

